

RECEIVED
FEB 19 1986

RECEIVED
FEB 19 1986

RECEIVED
FEB 19 1986

TOPIC TACK: parabolic quasi linear equation, parabolic equation numerical solution, finite-difference scheme, three-level scheme, two-level scheme

ABSTRACT: High-accuracy finite-difference scheme of the second order of approximation is constructed for the parabolic quasi-linear equation

$$\frac{\partial u}{\partial t} = f(t, x) \frac{du}{dx} + g(t, x)$$

in the rectangular domain $G(0 < t \leq T, 0 < x < L)$ with certain boundary and initial conditions. The stability of the finite-difference equation is studied by the method of the matrix factorization. The scheme is shown to be stable if the condition $|f(t, x)| \leq M$ is satisfied. The scheme is shown to be stable if the condition $|f(t, x)| \leq M$ is satisfied. The scheme is shown to be stable if the condition $|f(t, x)| \leq M$ is satisfied.

Card 1/2

VL 26314-6;

ACCESSION NR: AP5005559

of computation is analyzed. It is shown that when h and $l = h^2/\ell$, where h and ℓ are the dimensions of the mesh of a rectangular net satisfying certain conditions, the process of computation converged and numerical solutions of (1) and (2) with an error of the order of $O(h^4)$. The numerical solution of (1) and (2) with a small number of formulas is obtained by the method of successive approximations. The same method can be used for the solution of (1) and (2) if the following conditions are satisfied. The values of $u(t, x)$ calculated by means of these formulas are obtained with an error of the order of $O(h^4)$. It is asserted that the obtained results can be extended with certain insignificant modifications to the solution of the equation

$$\frac{\partial^2 u}{\partial x^2} = A(t, x) \frac{\partial u}{\partial t} + B(t, x) \frac{\partial u}{\partial x} + C(t, x, u). \quad (2)$$

Orig. art. has: 30 formulas.

[LK]

ASSOCIATION: Tbilisskiy gosudarstvennyy universitet (Tiflis State University)

SUBMITTED: 16Mar64

INCL: 00

SUB CODE: MA

NO REF Sov: 001

OTHER: 000

ATD PRESS: 3187

Card 2/2

L 51082-65 EWT(a) Pg-4 LIP(c)
ACCESSION NR: AP5011822

UR/0251/65/038/001/001: /0022

AUTHOR: Gordaziani, D. A.

TITLE: Use of rhomboid grids for solving the heat equation

SOURCE: AN GruzSSR. Soobshcheniya, v. 38, no. 2, 1965, 15-22

TOPIC TAGS: finite difference, differential equation /6

ABSTRACT: Under the assumption of a sixth order smooth solution of

$$\Delta u = A(t) \frac{du}{dt} + C(t, x, y) u, \quad \left(\Delta \equiv \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2} \right), \quad (1)$$

satisfying $\left. \begin{array}{l} u(0, x, y) = f(x, y), \quad (x, y) \in G, \\ u(t, x, y) = \varphi(t, x, y), \quad (x, y) \in \gamma, \quad 0 < t < T, \end{array} \right\} \quad (2)$

for $0 < t \leq T$ where G is a region in the x, y plane, γ is the boundary contour of G , $A(t) \geq \alpha > 0$, $f(x, y)$ and $\varphi(\cdot, x, y)$ are continuous and $f(x, y) = \varphi(0, x, y)$, $x, y \in \gamma$ and with $A_t^{(4)}, C_x^{(4)}, C_y^{(4)}$ continuous on $\bar{D} = \{(x, y) \in G, t \in [0, T]\}$,

Cord 1/2

L 51012-63

ACCESSION NR: AP5011822

the author studies an explicit finite difference scheme of high accuracy using a rhombic grid. He proves a theorem giving the rate of convergence of the solution of the difference scheme to that of the equation. Only second order formulas.

ASSOCIATION: Tbilisskiy gosudarstvennyy universitet (Tbilisi State University)

SUBMITTED: 24Jun64

ENCL: 00

SUB CONG: MA, TD

NO REF Sov: 003

OTHER: 000

ME
Card 2/2

L 100115-66 EWT(d) IJP(c)

ACC NR: AP6000731

SOURCE CODE: UR/0251/65/039/003/0535/0541

AUTHOR: Gordeziani, D. G.

ORG: Academy of Sciences, Georgian SSR, Tbilisi Mathematical Institute im. A. M. Razmadze (Akademiya nauk Gruzinskoy SSR, Tbilisskly matematicheskly institut)

TITLE: Use of a locally one-dimensional method for solving a multidimensional parabolic equation of order 2m

SOURCE: AN GruzSSR. Soobshcheniya, v. 39, no. 3, 1965, 535-541

TOPIC TAGS: differential equation, parabolic equation

ABSTRACT: The author shows the applicability of the locally one-dimensional method of A. A. Samarsky (Ob odnom ekonomichmom raznostnom metode resheniya mnogomernogo parabolicheskogo uravneniya v proizvol'noy oblasti. Zhurnal vychislitel'noy matematiki i matematicheskoy fiziki, 2, №. 5, 1962, 787-811) to the solution of

$$\frac{\partial u}{\partial t} = \sum_{i=1}^n L_i u_i \quad (1)$$

$$\left(u, \frac{\partial^2 u}{\partial y^2}, \dots, \frac{\partial^{2(m-1)} u}{\partial y^{2(m-1)}} \right) \Big|_S = (0, 0, \dots, 0) \quad (2)$$

$$u(0, x) = f(x), \quad x \equiv (x_1, x_2, \dots, x_p) \in G. \quad (3)$$

Card 1/2

ACC NR: AP6000731

He shows that under given conditions the difference problem

$$\theta L_{h\alpha} U^{q+\alpha/p} + (1-\theta) L_{h\alpha} U^{q+(n-1)/p} = \bar{U}_{I_q} \quad (0 \leq \theta \leq 1) \quad (4)$$

$$\begin{cases} \partial_x^{\alpha} U \\ x_0 = 0 \\ x_n = 1 \end{cases} = 0 \quad (q = 0, 1, \dots, m-1; \alpha = 1, 2, \dots, p), \quad t \in \omega \quad (5)$$

$$U(0, x) = f(x), \quad x \equiv (x^{(1)}, x^{(2)}, \dots, x^{(m)}) \in \bar{\omega} \quad (6)$$

has a unique stable solution which converges in mean to the solution of (1) - (3). This paper was presented by Sh. Ye. Mikeladze on 15 March 1965. Orig. art. has: 14 formulas.

SUB CODE: 12/ SUBM DATE: 15Mar65/ ORIG REF: 004

Card 2/2

GORDEZIANI, Karlo Shalvovich; GORDEZIANI, Marlen Shalvovich;
GAPRINDASHVILI, Iosif Silovanovich .

[Labeled atoms and their use in agriculture] [Mechenye
atomov i ikh primenenie v sel'skom khoziaistve. Tbilisi,
Sabchota Sakartvelo] 1965. 138 p. [In Georgian]
(MIRA 18:8)

GORDEZIANI, Karlo Shalvovich; GORDEZIANI, Marlen Shalvovich;
GAPRINDASHVILI, Iosif Silovanovich

[Labeled atoms and their use in agriculture] [Mechenye
atomov i ikh primenie v sel'skom khoziaistve. Tbilisi,
Sabchota Sakartvelo] 1965. 138 p. [In Georgian]
(MIRA 18:8)

RUKHADZE, D.A., inzh.; GORDEZIANI, N.N., inzh.

Determining the optimum height of high-basicity sinter
burdens. Stal' 20 no. 12:1074 D '60. (MIRA 13:12)
(Sintering)

MALYSHEV, S.I., inzh.; KHOSHTARIYA, Sh.F., inzh.; GLADKOSKOK, P.P., inzh.; RADCHENKO, F.G., inzh.; Prinimali uchastiye: BOKOLISHVILI, Sh.S.; RUKHADZE, R.I.; SHARASHIDZE, S.Sh.; BEREZHNOY, N.; GORDEZIANI, N.N.; RUKHADZE, D.A.; TATARADZE, Z.

Mastering the sintering of Dashkesan ores as acceptable charge for open-hearth furnaces. Stal' 20 no. 7:584-590 J1 '60. (MIRA 14:5)

1. Zakavkazskiy metallurgicheskiy zavod.
(Dashkesan--Iron ores) (Sintering)
(Open-hearth furnaces--Equipment and supplies)

RUKHADZE, D.A., inzh.; GORDEZIANI, N.N., inzh.

Blast furnace operations on natural gas. Stal' 20 no. 12:1074
D '60. (MIRA 13:12)

(Blast furnaces--Equipment and supplies)

KASHAKASHVILI, N.V.; GLADKOSKOK, P.P.; KHOSHTARIYA, Sh.F.; MINDELI, M.Sh.
Prinimali uchastiye: PARASTASHVILI, V.V.; KOBERIDZE, V.G.;
CHKHEIDZE, Z.A.; RUKHADZE, E.A.; KENKEBASHVILI, O.A.; SHARASHIDZE,
S. Sh.; GOGISHVILI, A.G.; MELKADZE, N.V.; DRAMASHVILI, A.V.;
GORDEZIANI, N.N.; ABRAMISHVILI, R.N.

Performance of Transcaucasia Metallurgical Plant blast fur-
naces operating on natural gas. Trudy GPI [Gruz.] no.4 all-23
"62 (MIRA 17:8)

KASHAKASHVILI, N.V.; SHARADZENIDZE, S.A.; MALYSHEV, S.I.; CHKHEDZE, Z.A.
GIBRADZE, Sh.S.; KHOSHTARIYA, Sh.F.; RUKHADZE, D.A.; SHARASHIDZE,
S. Sh. Prinimali uchastiya: SHENGELAYA, V.; OKROMCHEDLISHVILI,
Sh.; POPIASHVILI, Sh.; LOLUA, K.; MINDELI, M.; TSKHELISHVILI, D.;
GORDEZIANI, N.; ODIKADZE, Ch.; TATARADZE, Z.; KHUTSISHVILI, A.

Production and use of highly basic, open-hearth furnace sinters
from Dashkesan iron ore. Trudy GPI [Gruz.] no.4:25-32 '62
(MIRA 17:8)

RUKHADZE, D.A., inzh.; GORDEZIANI, N.N., inzh.

Sintering high-basicity mixtures at the Rustavi metallurgical plant.
Stal' 23 no.6:99 Je '63. (MIRA 16:10)

1. Rustavskiy metallurgicheskiy zavod.

USSR / Human and Animal Physiology. Heart.

T

Abs Jour : Ref Zhur - Biol., No 15, 1958, No. 70156

Author : Gordeziani, Sh. G.

Inst : Tbilisi Medical Institute

Title : Collaterals and Collateral Circulation in the Heart in
Experimental Omentocardioectomy

Orig Pub : Tr. Kafedry operativn. khirurgii i topogr. anatomi. Tbilissk. med. in-t, 1956, Vol 1, 181-187

Abstract : In 14 dogs a ligature was applied to the descending branch of the left coronary artery, and the omentum was sutured to the myocardium. In ten days, three months, and six months, corrosion preparations were made. By six months after operation, vascular anastomoses between the myocardium and the omentum could be seen.

Card 1/1

54

Gordeziani, Sh.

MAYZIL', F.

"Material on surgical treatment of coronary insufficiency" by
Sh.G. Gordeziani. Reviewed by F. Maizil'. Khirurgiia 34 no.6:143
Je '58 (MIRA 11:8)

(CORONARY VESSELS--SURGERY)
(GORDEZIANI, Sh.G.)

GORDI, U.

33915. Mikrovolnovaya Spyektroskopiya(Pyer. S Angl.) Uspyeekhi Fiz. Nauk, T, XXXIX,
Vyp. 2, 1949, C.201-98. --Bibliogr: C. 293-98.

SE: Letopis' Zhurnal'nykh Statej, Vol. 46, Moskva, 1949.

GORDIAN, N.M.

USSR/Microbiology - Antibiosis and Symbiosis. Antibiotics.

F-2

Abs Jour : Ref Zhur - Biologiya, No 7, 1957, 26291

Author : Margolina, M.I., Gordian, N.M., Kamraz, M.I.

Inst : Kharkov Institute of Vaccines and Serums

Title : Experimental Study of the Effect of Garlic Phytoncides
on Dysenteric Bacteria.

Orig Pub : Khar'kovsk. n.-i. in-ta vaktsin i syvorotok, 1955, 22,
75-79

Abst : All 123 of the dysentery bacteria cultures were found
to be sensitive to garlic phytoncides (I). Culture
growth in bouillon was arrested by garlic juice when
diluted to 1: 400 - 1: 80. The greatest sensitivity to
I was evidenced by the Grigoryev-Shig dysenteria bacil-
lus. No difference was noted in the sensitivities of
freshly cultured and museum strains. Culture in a me-
dium containing I did not increase the resistance of the
cultures. Continued cultivation in media containing I

Card 1/2

USSR/Microbiology - Antibiosis and Symbiosis. Antibiotics.

F-2

Abs Jour : Ref Zhur - Biologiya, No 7, 1957, 26291

brought about modifications in the morphological properties of dysenteric cultures (large numbers of long filamentous and coccus-type forms appeared, R-colonies predominated), but biochemical properties and agglutinability remained the same. I is not toxic for white mice. Over one month, the activity of I decreased by 2, and by 4 to 10 times in three months.

Card. 2/2

GORDIC, Z.

Local roads in Serbia.

p. 15 (Put I Saobracaj) No. 7, July 1957
Belgrade, Yugoslavia

SO: Monthly Index of East European Accessions (EEAI) LC. Vol. 7, no. 4,
April 1958

GORDIKOV, A.V.; ROSSOMAKHIN, M.V.

Transverse gradients of the water surface of an inundated
flood plain (exemplified by the Irtysh River). Trudy GGI
no.88:109-124 '61. (MIRA 15:2)
(Irtysh River-Hydrology)

ANDREYEV, S.G.; GORDIKOV, N.V.; RUMYANTSEV, A.T., red.; KOREYSHO,
Ye.G., red.; DEYIEVA, V.M., tekhn.red.

[Local fertilizers; advanced practices in their acquisition
and usage] Mestnye udobreniya; peredovoi opyt nakopleniya
i primeneniia. Moskva, Gos.izd-vo sel'khoz.lit-ry, 1960.
206 p. (MIRA 14:2)
(Fertilizers and manures)

BUZENKOV, G.M.; GORDIKOV, N.V.; ANDREYEV, S.G.; KOREYSHO, Ye.G., red.;
GOR'KOVA, Z.D., tekhn. red.

[Corn in new regions; advanced cultivation practices] Kukuruza v
novykh raionakh; peredovoi opyt vozidelvaniia. Moskva, Gos. izd-
vo sel'khoz. lit-ry, 1960. 136 p. (MIRA 14:6)
(Corn (Maize))

ANDREYEV, S.V., prof.; KRAVCHENKO, A.T., prof.; NAUMENKO, V.G., kand. med. nauk;
Prinimali uchastiye: GORDILOVA, V.V., prof.; YESIPOVA, I.K., prof.;
SMOL'YANINOV, V.M., prof.; SOKOLOV, M.I., prof.

Dissertations on pathological and microbiological problems; current
state and future prospects. Sov. med. 27 no.6:147-151 Je '64.
(MIRA 18:1)

GORDIN, A.M.

AID P - 3002

Subject : USSR/Electricity

Card 1/1 Pub. 29 - 17/28

Authors : Tarakanova, Ye. N., I. I. Ryabushkin, and A. M. Gordin,
Engs.

Title : Movable installations of power capacitors

Periodical : Energetik, 6, 26-27, Je 1955

Abstract : A major work was done at the establishments of the Karaganda Coal Combine in order to raise the power factor. The basic measure consisted in introducing synchronous motors in ventilating and compressor installations and also synchronous converters and static capacitors at the central substations of the combine. The author describes the details of these installations. Three diagrams, one table.

Institution : None

Submitted : No date

GORDIN, A.Yu.; MILL', L.A.

Industrial training shops. Politekh.obuch. no.5;11-17 My '59.
(MIRA 12:7)

1. Srednyaya shkola No.544 g.Noskvy.
(Moscow--Manual training)

GORDIN, B.I.

Scientific and technical conference on the manufacture of high-voltage
apparatus. Elektrotekhnika 35 no.4 1964 Ap '64. (MIRA 17:4)

"APPROVED FOR RELEASE: 06/13/2000

CIA-RDP86-00513R000516130001-4

GORDIN, B.L.

DECEASED

c 1959

1951/3

SEE ILC

HYGIENE AND SANITATION

APPROVED FOR RELEASE: 06/13/2000

CIA-RDP86-00513R000516130001-4"

GORDIN, B.S., inzhener.

Manufacture of wall brick from power plant slag. Biul.stroi.tekh. 10 no.12:
(MLRA 6:8)
13-14 Jl '53.
(Bricks) (Slag)

GORDIN, E.I.

The Beslan corn combine. Uch. zap. Ped. inst. Gertis: 169:193-199
'59. (MDR 14:1)
(Beslan—Food industry)

GORDIN, G.A.

Berlyand, A.S. and Gordin, G.A. "On a method of determining the speed of blood circulation",
Vracheb. delo, 1949, No. 1, paragraphs 33-36.
SO: U-3042, 11 March 53, (Letopis 'nykh Statey, No. 9, 1949)

SORKINA, A.I.; GORDIN, G.B.

Late results of operative treatment of a serious form of
hyperparathyroid osteodystrophy with calcareous metastases.
Probl. endok. i gorm. 11 no.1:58-60 Ja-F '65.

(MIRA 18:5'

1. Kafedra obshchey khirurgii (zav. - prof. A.I. Sorkina)
Irkutskogo meditsinskogo instituta na baze gorodskoy kli-
nicheskoy bol'nitsy (glavnnyy vrach A.F. Demidova).

FILIPPOV, N.A.; GORDIN, I.M., inzhener, redaktor.

[Bricklaying by a 4-man team] Kирпичная кладка звеном-четверкой.
Leningrad, Gos. izd-vo lit-ry po stroitel'stvu i arkhitekture, 1953. 41 p.
(MLRA 7:6)

(Bricklaying)

GORDIN, Iosif Mikhaylovich; VODAKOV, A.A., inzhener, nauchnyy redaktor;
KAPLAN, M.Ya., redaktor; FUL'KIM, Ye.A., tekhnicheskiy redaktor.

[Extensible panel scaffolding for bricklaying] Panel'nye razdvish-
nye podmosti dlia kirkichnoi kladki. Leningrad. Gos. izd-vo lit-ry
po stroitel'stvu i arkhitektуре, 1954. 46 p. (MLRA 8:1)
(Bricklaying) (Scaffolding)

ZHELTIKOV, V.F.; GORDIN, I.M.; SPIVAKOV, M.S.; ALEXSEIEV, N.P.; VODAKOV, A.A.

Adjustable scaffolding for bricklaying. Rass. i izobr. predl. v stroi.
no.91:7-9 '54. (MIRA 8:8)

1. Trest Lainmekhmontashstroy ispolkoma Lengorsoveta.
(Bricklaying) (Scaffolding)

GORDIN, I. M.

BISPALOV, Ivan Vasil'yevich, GORDIN, I. M., inzhener, nauchnyy redaktor;
KAPLAN, M.Ya., redaktor izdatel'stva; PUL'KINA, Ye.A., tekhnicheskiy
redaktor

[Assembling precast concrete elements; for work superintendents and
foremen] Montazh sbornogo zhelezobetona dlja proizvoditelei rabot i
masterov. Leningrad, Gos.izd-vo lit-t-ry po stroit. i arkhit., 1957.
131 p.

(MLRA 10:9)

(Precast concrete construction)

GORDIN, I.M.; MURATKHAN, V.P.; PANOV, V.K.; KRAVTSOV, G.Ya., red.;
PARAKHINA, N.L., tekhn. red.; PROKOF'YEVA, L.N., tekhn.red.

[Organization and performance of land improvement construction work] Organizatsiia i proizvodstvo meliorativno-stroitel'nykh rabot. Moskva, Sel'khozizdat, 1963. 327 p.
(MIRA 17:3)

GORDIN, L.Yu.; KOROTOV, V.M.

"Tales of the life of the brain." Z.Kosenko, A. Remezova. Reviewed
by L.IU. Gordin, V.M. Korotov. Est. v shkole no.3; 86-89 Ny-~~36-37~~
(MIRA 7:7)

1. Uchitel' shkoly no.700 g. Moskvy (for Gordin) 2. Uchitel'
shkoly no.200 g. Moskvy (for Korotov)
(Kosenko, Z.) (Remezova, A.) (Brain)

GORDIN, M.D., BORISOVICH, G.F.

Tasks of the synthetic rubber industry in the sixth five-year
plan. Khim. nauka i prom. 2 no.3:274-279 '57. (MLRA 10:8)
(Rubber industry)

GORDIN, M.D.

64 - 7 - 2/12

AUTHORS: Gordin, M. D., Borisovich, G. F.

TITLE: The Industry of Synthetic Rubber (Caoutchouc) - on the Occasion of the 40th Anniversary of the Soviet Republic (Promyshlennost' sinteticheskogo kauchuka k 40-letiju Sovetskogo Gosudarstva).

PERIODICAL: Khimicheskaya Promyshlennost', 1957, Nr 7, pp.(392)8 - (396)12 (USSR)

ABSTRACT: As early as in the years around 1920, Soviet scientific experts succeeded in producing synthetic rubber (caoutchouc) from "butadien" (obtained from ethyl alcohol by means of a one-stage catalysis) which was subsequently subjected to polymerization under the influence of metallic sodium. In Spring 1931 the Soviets began with the construction of the first factories in Yaroslavl', Voronezh and Yefremov; and on July 4, 1932, the first 400 kg of synthetic Soviet rubber were obtained. Large scale production in other countries was carried out much later only: In Germany, in 1937, in the United States only in 1942. A survey of the further development up to the present is given. The projects for the period

CARD 1/3



The Industry of Synthetic Rubber (caoutchouc) - on the 64 - 7 - 2/12
Occasion of the 40th Anniversary of the Soviet Republic

of 1951 to 1955 could not be accomplished for lack of both material and workmen. But the Soviets want to make up for this, now. The assortment of synthetic rubber has become very rich: SKB-sodium-butadiene caoutchouc, DAB-butadiene-latex DVKhB-70- butadiene-Vinylidene-chloride-Latex, butadiene-nitril-caoutchouc SKN of three different makes, polyisobutylene, some makes of Nairit, SKBM, chloroprene-latex, butadiene-styrol-caoutchouc SKS 30, and many others. The butadiene-methyl-styrol-caoutchouc (SKMS 30) is produced on an industrial basis in the Soviet-Union only. It is used on a large scale for the manufacture of tires. Further the oil-filled caoutchouc SKS-30 AM is produced, the technological properties of which by far surpass the "Butadien"-Styrol-caoutchouc. In 1956 the production of Silicon-caoutchouc (SKT) was substantially increased. It retains its properties at a temperature of - 60 to - 250°C. It is water, -acid- and oil-resistant and is

CARD 2/3

The Industry of Synthetic Rubber (caoutchouc) - on the 64 - 7 - 2/12
Occasion of the 40th Anniversary of the Soviet Republic

proof against ultra-violet radiation. In the second half of 1956 the production of brombutyl-caoutchouc (for the insulating layer in solid tires) was begun.

AVAILABLE: Library of Congress

CARD 3/3



CORDIN, M.M., inzh.

Puller tool for the driving wheel of the S-80 and S-100 tractors.
Mekh.stroi. 19 no.3:26 Mr '62. (MIRA 15:3)
(Tractors)

SHFINDLER, D.L.; GORDIN, M.N.

Effect of cholagogues on the milk and butterfat yield of
cows. Uch. zap. Kazakh. un. 41:186-187 '61. (MIRA 16:6)
(CHOLAGOGUES) (DAIRY CATTIE--FEEDING AND FEEDS)

GORDIN, M.N.; KARIMOVA, R.F.

Hypotensive and some other properties of the herbage of the
periwinkle Vinca minor. Vest. AN Kazakh. SSR. 19 no.5:91-95
My '63. (MIRA 17:7)

Gordin, M. N.

MD

The effect of darminol on the cardiovascular system.
M. N. Gordin, Nauch. Izv. Kazakh. Med. Inst. 1953,
No. 11, T41-0; Referat. Zhur. Khim., Biol. Khim. 1955, No.
2392, B. S. Levine

GARDIN, M.N.

Local anesthetic and other pharmacological properties of the stereoisomers of 2,5-dimethyl-4-piperidyl benzoate. N. N. Gardin and G. I. Samorina (V. M. Molotov Kazakh. Univ., Alma-Ata). Izv. Akad. Nauk KazSSR, Ser. Fiz. i Mat. No. 4, 97-104 (1954) [in Russian]. —The 3 forms of 2,5-dimethyl-4-piperidyl benzoate (m. 205-6°, 157-8°, and 253-4°) were investigated. All 3 forms cause local anesthesia after application to a rabbit eye or skin of a frog; terminal anesthesia is best shown by the 3rd form (called C or γ). Ag. solns. cause anesthesia by infiltration. The order of toxicity rises from A to B to C (α , β , γ). Subcutaneous administration causes lowering of blood pressure; all contraction of peripheral blood vessels of the hind legs of a frog when used in soln. of smooth muscle and protracted rabbit intestine. None is suitable for clinical infiltration owing to toxicity.

G. M. Kosolapoff

GORDIN, M.N.

Mechanism of the reaction of peripheral blood vessels to strophantin. Farm. i toks. 18 no.6:44-47 N-D '55. (MLRA 9:3)

1. Kafedra farmakologii (zav.-prof. I.I. Sivertsev) Kazakhskogo gosudarstvennogo meditsinskogo instituta imeni V.M. Mosotova.

(STROPHANTHID, effects,

on blood vessels of amputated extremity with neural connection with body, conditioned reflex mechanism of action)

(BLOOD VESSELS, effect of drugs on,

strophantin, in amputated extremity with neural connections with body, conditioned reflex mechanism of action)

(REFLEX, CONDITIONED,

conditioned reactions of blood vessels to strophantin in amputated extremity with neural connections with body)

GORDIN, M.N.; TURGANBAYEV, A.T.

The effect of santonin on intestinal contraction [with summary in English]. Farm. i toks. 21 no.1:71-73 Ja-F '58. (MIRE 11:4)

1. Kafedra farmakologii (zav.-prof. I.I. Sivertsev) Kazakhskogo gosudarstvennogo meditsinskogo instituta i rentgenovskiy kabinet Instituta klinicheskoy i eksperimental'noy khirurgii AM Kazakhskoy SSR.

(ANTHELMINTICS, effects

santonin on intestinal motility & contractions in cats (Rus)

(INTESTINES, physiology

motility & contractions, eff. of santonin on cats (Rus)

GORDIN, M.N., kand.med.nauk

Change in body reaction to the influence of local anesthetics during various periods in radiation sickness. Zdrav. Kazakh. 21 no.1:65-69 '61. (MIRA 14:3)

1. Iz kafedr farmakologii, (zav. - professor I.I.Sivertsev [deceased]) rentgenologii i radiologii (zav. - doktor meditsinskikh nauk S.B. Balmukhanov) Kazakhskogo meditsinskogo instituta.
(LOCAL ANESTHESIA) (RADIATION SICKNESS)
(BODY TEMPERATURE)

GOVOROV, A.A.; KOSHKIN, V.A.; GORDIN, O.V.; TUZOVSKIY, A.I.; SAKHAROVA, N.A.;
LYMAR', A.I.

Effect of the temperature of the end of rolling on the mechanical
properties of rail steel. Izv. vys. ucheb. zav.; chern. met.
6 no.8:137-140 '63. (MIRA 16:11)

1. Sibirskiy metallurgicheskiy institut i Kuznetskiy
metallurgicheskiy kombinat.

GRDINA, Yu.V.; KOSHKIN, V.A.; GORDIN, O.V.; SAKHAROVA, N.A.

Inoculation of rail. steel. Izv. vys. ucheb. zav.; chern. met.
6 no.10:129-133 '63. (MIRA 16:12)

1. Sibirskiy metallurgicheskiy institut.

GRDINA, Yu.V.; GORDIN, O.W.

Characteristics of the mechanism of inoculating rail steel.
Izv. vys. ucheb. zav.; chern. met. 6 no.12:152-157 '63.
(MIRA 17:1)

1. Sibirsckiy metallurgicheskiy institut.

GRDINA, Yu.V.; GORDIN, O.V.

Dependence of impact toughness in rail steel on the finishing temperature. Izv.vys.ucheb.zav., chern.met. 8 no.8:114-117 '65.
(MIRA 18:8)

1. Sibirskiy metallurgicheskiy institut.

L 212(8-66 EWT(m)/ETC(f)/EPF(n)-2/ENG(m)/I/EWP(t)/EWP(k)	IJP(c) JD/HW/JG/WB
ACC NR: AP6007928	SOURCE CODE: UR/0148/66/000/002/0119/0121
AUTHOR: Grdina, Yu. V.; Tarasko, D. I.; Dadochkin, N. V.; Gordin, O. V.	
ORG: Siberian Metallurgical Institute (Sibirskiy metallurgicheskiy institut)	87 86
TITLE: Rapid oxidation-free heating of metals for rolling	B
SOURCE: IVUZ. Chernaya metallurgiya, no. 2, 1966, 119-121	
TOPIC TAGS: steel, refractory metal, molybdenum, tungsten, niobium, steel heating, refractory metal heating, oxidation free heating, metal oxidation, oxidation prevention / 60S2 steel, 45G steel, steel 5	
<p><u>ABSTRACT:</u> In a search for an effective and inexpensive method of heating steels and refractory metals for forging, rolling, and extrusion, molten glass has been tested as a heating medium. Specimens of steels 60S2, 45G, St5, and molybdenum, tungsten and niobium were heated up to 1100–1350°C in molten glass (71.88% SiO₂, 1.11% Al₂O₃, 1.5% Fe₂O₃, 7.32% CaO, 2.27% MgO, 14.15% K₂O + Na₂O) for 5 min to 3 hr. No sign of oxidation was observed on any specimen. On the other hand, 60S2 steel conventionally heated to 1150°C was extensively oxidized after holding 20 min. This type of steel, badly affected by decarbonization in conventional heating, showed no sign of decarbonization when</p>	
Card 1/2	UDC: 669.046—947

GORDIN, P.V., inzh.

Studying the tension of the basic parts of the D-170 diesel
engine. Trakt. i sel'khozmash. no.11:4-6 N '65.
(MIRA 18:12)
1. TSentral'nyy nauchno-issledovatel'skiy dizel'nyy institut.

GORDIN TS d.
GORDIN, TS. G. inzh.

Lowering the cost of constructing industrial buildings by modifying
the crane system. Biul. stroi. tekhn. 14 no.12:16 D '57. (MIRA 11:1)

1. Leningradskoye otdeleniye Gosudarstvennogo proyektnogo instituta
Proyektstal'konstruktsiya.
(Building--Costs) (Cranes, derricks, etc.)

LEMLEKH, Izrail Moiseyevich; GORDIN, Veniamin Avseyevich; VAGIN, A.A.,
red.; ATTOPOVICH, M.K., tekhn. red. [deceased]

[High temperature preheating of air in ferrous metallurgy] Vy-
sokotemperaturnyi nagrev vozdukh v chernoi metallurgii. Mo-
skva, Metallurgizdat, 1963. 352 p. (MIRA 16:3)
(Air preheaters)
(Metallurgical furnaces)

GORDIN, V.A.

Standardization bureau at the Rybinsk Road-Machinery Plant.
(MIRA 17:4)
Standartizatsiia 27 no.12:40-41 D '63.

S/137/61/000/001/013/043
A006/A001

Translation from: Referativnyy zhurnal, Metallurgiya, 1961, No. 1, p. 23,
1D198

AUTHOR: Gordin, V.B.

TITLE: Problems of Calculating a Hydraulic Forging Press With Multipli-
cator and Pump-Accumulator Drives

PERIODICAL: V. sb. "Osnovn. vopr. razvitiya kuznechno-shtamp. proiz-va", Moscow,
1958, pp. 553 - 575

TEXT: The operational stroke, the back stroke and the filling stroke are calculated for accumulator and multiplicator drives. It is shown that the speed of the operational stroke depends, basically, on the dimensions of the pressure pipeline, the moving masses and the law of changes in the resistance of the forging. To maintain a constant vapor pressure, the dimensions of the vapor inlet valve have to be increased. It is recommended to use a pneumatic pistonless accumulator in presses intended to be used for processes with falling technological resistance. The hoisting force depends on the hoisting rate, pressure in the

Card 1/2

S/137/61/000/001/013/043
A006/A001

Problems of Calculating a Hydraulic Forging Press With Multipliator and Pump-Accumulator Drives

filling tank and the dimensions of the reverse pipe. The given coefficient of resistance of the reverse pipe is determined from the given hoisting speed. The pipe is calculated from the found coefficient. The speed of the idle stroke is determined from the dimensions of the filling pipe and the pressure in the filling tank. For vertical presses the pressure in the filling tank should be used equal to 4.5 kg/cm². ✓

Ye. M.

Translator's note: This is the full translation of the original Russian abstract.

Card 2/2

PHASE I BOOK EXPLOITATION

SOV/4713

Gordin, Vul'f Borisovich, Candidate of Technical Sciences
Teoreticheskiye osnovy gidravlicheskogo rascheta kovochnykh pressov
 (Theoretical Principles of Designing Hydraulic Forging Presses)
 Moscow, Mashgiz, 1960. 83 p. Errata slip inserted. 3,000
 copies printed.

Reviewers: I. M. Din, Engineer, and E. I. Goloskov; Ed.: V. A.
 Mikheyev, Engineer; Managing Ed. for Literature on Machine-
 Building Technology (Leningrad Department, Mashgiz); Ye. P.
 Naumov, Engineer; Ed. of Publishing House: M. A. Chfas; Tech.
 Ed.: O. V. Speranskaya.

PURPOSE: This book is intended for design engineers of hydraulic
 presses and mechanical engineers in hydraulic-press shops and
 may be useful to students of mechanical engineering in schools
 of higher education.

COVERAGE: The book contains an analysis of the working cycle of a
 hydraulic forging press and calculation formulas for determining
 the dimensions of the working parts of the press and the drive.

Card 1/3

The calculation formulas presented in the book show the influence of separate parameters of the press unit on its performance. The formulas also make it possible to select a suitable press arrangement, to determine the pressure of the hydraulic fluid and the steam pressure for steam-hydraulic presses, and can be used as an aid for making judgments as to the merits of various designs. No personalities are mentioned. There are 26 references, all Soviet.

TABLE OF CONTENTS:

Introduction	3
Ch. 1. The Working Stroke	10
Ch. 2. The Opening Stroke	33
Ch. 3. The Filling Stroke (The Idle Downstroke)	41
Ch. 4. Investigating the Influence of Certain Parameters of the Unit on the Performance of the Press	48

Card 2/3

GORDIN, V.B.

PHASE I BOOK EXPLOITATION

SOV/5658

Ivanov, Aleksandr Petrovich, Candidate of Technical Sciences, and
Viktor Dmitriyevich Lisitsyn, Candidate of Technical Sciences,
eds.

Modernizatsiya kuznechno-shtampovochnogo oborudovaniya (Modernization
of Die-Forging Equipment) Moscow, Mashgiz, 1961. 226 p.
Errata slip inserted. 10,000 copies printed.

Reviewer: V. Ye. Nedorezov, Candidate of Technical Sciences; Ed.
of Publishing House: T. L. Leykina; Tech. Ed.: A. A. Bardina;
Managing Ed. for Literature on Machine-Building Technology
(Leningrad Department, Mashgiz): Ye. P. Naumov, Engineer.

PURPOSE: This book is intended for foremen, machinists, designers,
and process engineers concerned with the modernization and de-
signing of die-forging equipment. It may also be used by students
at schools of higher education.

COVERAGE: The book contains material presented at the Conference

Card 1/8

Modernization of Die-Forging Equipment

SOV/5658

on Problems in the Modernization and Operation of Die-Forging Equipment, held in November 1958 in Leningrad. The Conference was called by Leningradskiy Sovet narodnogo khozyaystva, Sektsiya obrabotki metallov davleniyem Leningradskogo oblastnogo pravleniya NTO Mashprom (Leningrad Council of the National Economy, Section of Metal Pressworking at the Leningrad Oblast Board of the Scientific and Technical Society of the Machine Industry) and Leningradskiy mekhanicheskiy institut (Leningrad Mechanical Engineering Institute). Actual problems in the modernization, operation, and repair of die-forging equipment are described. Analyses are provided for problems involved in the mechanization and automation of die-forging and stamping operations. Also included are practical data to be used in the modernization of equipment. No personalities are mentioned. There are 59 references: 56 Soviet, 2 German, and 1 English.

TABLE OF CONTENTS:

Foreword

3

Card 2/8

Modernization of Die-Forging Equipment

SOV/5658

Ch. I. General Problems in the Modernization of Die-Forging Equipment	
1. Basic trends in the modernization of die-forging equipment (V. B. Gordin, Candidate of Technical Sciences)	5
2. The requirements for die-forging equipment (A. P. Ivanov, Candidate of Technical Sciences)	5
	8
Ch. II. Modernization of Forging and Die-Forging Steam Hammers	18
1. Hammers and their role in modern die-forging equipment (Z. M. Ginzburg, Engineer)	18
2. The modernization of steam-distributing devices of hammers (A. L. Ashkinazi, Candidate of Technical Sciences, and I. I. Kozhinskiy, Engineer)	18
3. Modernization of hammer control and drive (A. L. Ashkinazi, Z. I. Ginzburg, and K. K. Yekimov, Engineer)	19
4. Modernization and repair of foundations and anvil blocks of hammers (Yu. V. Belyayev, Candidate of Technical Sciences, Z. M. Ginzburg, and I. I. Kozhinskiy)	26
	31

Card 3/8

Modernization of Die-Forging Equipment

SOV/5658

5. Modernization and repair of hammer frames and guides (V. A. Zhivchikov, Engineer, and I. I. Kozhinskiy)	38
6. Modernization and repair of hammer cylinders and piston rods (Z. M. Ginzburg, V. A. Zhivchikov, I. I. Kozhinskiy, A. M. Kaznacheyev, and M. V. Tilinskiy)	41
7. Modernization and repair of rams (I. I. Kozhinskiy)	50
8. Lubrication of hammers (I. A. Gorbunov, I. I. Kozhinskiy, and A. I. Kaznacheyev)	53
 Ch. III. Modernization of Steam-Hydraulic and Hydraulic Presses	
1. Modern trends and the outlook for modernization of hydraulic presses (A. L. Ashkinazi and V. B. Gordin)	56
2. The ways for decreasing the weight and overall dimensions of hydraulic presses (Yu. P. Kyz'ko, Engineer)	58
3. Modernization of steam-hydraulic "United" 2,000-ton forging press (B. P. Vasil'yev and V. A. Yelezov, Engineers)	63
4. Automation of steam-hydraulic "United" presses (S. P. Moiseyev, Engineer)	71

Card 4/8

Modernization of Die-Forging Equipment

SOV/5658

- Ch. IV. Modernization of Mechanical Crankshaft Presses 78
1. Basic methods for the complete modernization of crankshaft presses (M. A. Goncharenko, Engineer, and V. D. Lisitsyn, Candidate of Technical Sciences) 78
 2. Modernization of the drives of mechanical presses (A. P. Ivanov and V. B. Gordin, Candidates of Technical Sciences) 87
 3. Modernization of engaging and disengaging mechanisms of crankshaft presses (V. A. Zhivchikov, A. M. Kaznacheyev, and V. D. Lisitsyn) 89
 4. Modernization of control system of mechanical presses (V. D. Lisitsyn) 10
 5. Modernization and repair of individual subassemblies and parts of mechanical presses (I. I. Kozhinskiy, and V. D. Lisitsyn) 10
 6. Modernization of mechanical presses for the purpose of protecting them against overloading (Yu. M. Buzikov, Engineer) 11
 7. Safety technique in the modernization of mechanical presses (V. D. Lisitsyn) 12

Card 5/8

Modernization of Die-Forging Equipment

SOV/5658

Ch. V. Modernization of Horizontal-Forging Machines [Upsetters], Percussion Presses, and Shears	133
1. Modernization of horizontal-forging machines (V. A. Zhivchikov and I. I. Kozhinskiy)	133
2. Modernization of power-screw percussion presses (I. I. Kozhinskiy, and A. M. Kaznacheyev)	141
3. Modernization of eccentric shears for blanking operations (I. I. Kozhinskiy and V. N. Cherkasov, Engineer)	144
Ch. VI. Mechanization of Forging and Hot Die-Forging Operations in the Modernization of Hammers and Hydraulic Presses	149
1. Mechanisms and equipment for forging and die forging on hammers (K. K. Yekimov, Engineer)	149
2. Mechanisms and equipment for press-forging (K. K. Yekimov, and S. P. Moiseyev)	155
Ch. VII. Mechanization and Automation of Stamping Operations in The Modernization of Crankshaft Presses	160

Card 6/8

Modernization of Die-Forging Equipment

SOV/5658

1.	Trends in application of mechanizing and automatizing devices in the modernization of presses (V. D. Lisitsyn and M. A. Goncharenko)	160
2.	Mechanical devices for feeding band and strip stock (M. A. Gutnik, Engineer, V. D. Lisitsyn, and Ye. S. Nazarenko, Engineer)	163
3.	Mechanical devices for feeding piece-blanks (V. D. Lisitsyn, and Ye. S. Nazarenko)	177
4.	Fully automated [production] lines (E. E. Roytershteyn, Engineer)	186
Ch. VIII. Experimental Investigation of Die-Forging Equipment		191
1.	General sequence for the calculation and design of machines in the modernization of die-forging equipment (A. P. Ivanov)	191
2.	Basic problems of the drive-system dynamics and of the automatic feed of stock in the modernization of presses (A. P. Ivanov and Ye. S. Nazarenko)	193

Card 7/8

Modernization of Die-Forging Equipment

SOV/5658

3. Methods and means for the experimental investigation of
die-forging equipment (V. I. Zaytsev and M. P. Pavlov,
Candidates of Technical Sciences) 203
223

Bibliography

AVAILABLE: Library of Congress

VK/wrc/ec
11-7-61

Card 8/8

ACC NR: AT7003268

(N)

SOURCE CODE: UR/2563/66/000/263/0079/0088

AUTHORS: Gordin, V. B.; Yefimov, I. A.

ORG: none

TITLE: Determining the parameters of apparatus for finish rolling of blades

SOURCE: Leningrad. Politekhnicheskiy institut. Trudy, no. 263, 1966. Mashiny i tekhnologiya obrabotki metallov davleniyem (Machinery and technology of metalworking by pressure), 79-88

TOPIC TAGS: cold rolling, turbine blade, rolling mill, metal forming press, steel alloy, metal deformation hardness, steel/ EI765 steel, 20 steel, U10A steel, 2Kh13 steel

ABSTRACT: Determination of the parameters of a cold-rolling mill for turbine blades of 90 x 500 mm of EI765 steel (see Fig. 1) is discussed. The specific flow pressure and maximum allowable deformation were determined with specimens of EI765 steel with a width of 16 mm and thicknesses of 3, 4, 7, 9, 11, and 14 mm. The hardness was HRC 26, and the surface roughness was V 7. The blocks were made of U10A steel heat-treated to HRC 62. The degree of deformation at which failure of the specimens occurred increased with a decrease in thickness. The allowable degree of deformation was found to be 8.5% (see Fig. 2). Specimens of 20 and 2Kh13 steel were also used in determining the torque required for blade twisting. A formula is given for determining the

Card 1/3

ACC NR: AT7003268




Fig. 1. Kinematic diagram of cold-rolling mill for turbine blades

Card 2/3

ACC NR: AT7003268




Fig. 2. Specific flow pressure p versus degree of deformation ϵ for specimens of various thicknesses

clamping force. The force required with the described rolling mill is lower by a factor of 28 than that required with mechanical presses. Docent A. P. Atroshenko and engineer Yu. I. Yegorov participated in the experimental work. Orig. art. has: 6 graphs, 2 diagrams, and 12 formulas.

SUB CODE: 13/ SUBM DATE: none/ OTH REF: 001
101

Card 3/3

S/078/62/007/003/019/019
B110/B138

AUTHORS: Ugay, Ya. A., Gordin, V. I.

TITLE: Production and investigation of some of the properties of
 Hg_3Sb_2

PERIODICAL: Zhurnal neorganicheskoy khimii, v. 7, no. 3, 1962, 703 - 705

TEXT: Hg_3Sb_2 , which is a chemical analogy to the metallides Zn_3Sb_2 and Cd_3Sb_2 , could not be produced directly from its elements by S. A. Vekshinskiy's method (Novyy metod metallograficheskogo issledovaniya splavov (New method for the metallographical study of alloys), GONTI, 1944) Stibine, obtained by the action of hydrochloric acid solution of $SbCl_3$ on Mg metal, was passed through a mixture of $HgCl_2$ with sugar. A tall molybdenum glass column 3 cm in diameter was filled up to 2/3 with Mg metal type Mr-1 (Mg-1). $CaCl_2$ on a porous diaphragm at the top of the column was ice cooled from outside. A No. 1 Schott funnel inserted in the column contained twice recrystallized $HgCl_2$ mixed with sugar. The hydro-

Card 1/3

S/078/62/007/003/019/019
B110/B138

Production and investigation...

chloric acid solution of $SbCl_3$, introduced into the lower end of the column produced: $SbCl_3 + 3HCl + 3Mg = 3MgCl_2 + SbH_3 \uparrow$. SbH_3 was dried with $CaCl_2$ and reacted as follows: $3HgCl_2 + 2SbH_3 = Hg_3Sb_2 + 6HCl \uparrow$. The reaction took 2 - 3 hrs. The specific gravity of the powdery heavy gray Hg_3Sb_2 , determined pyknometrically, was 6.0 g/cm^3 . When heated in air Hg_3Sb_2 decomposes to mercury and antimony oxides around $400^\circ C$, and if heated in vacuum, into its elements at above $450^\circ C$. It is practically insoluble in water, alkali, and hydrochloric acid, partly soluble in concentrated HNO_3 , and highly soluble in boiling H_2SO_4 and aqua regia. When left in air it moistens after 2-3 weeks and Hg drops separate. Its electrical resistivity, by the compensation method and a $\pi\pi\pi\pi$ -1 (PPTV-1) potentiometer measured on a tablet pressed from the powder (250 kg/cm^2), was $10^{12}\text{ ohms}\cdot cm$. In cast Hg_3Sb_2 at room temperature conductivity is $\sim 10^{-11}\text{ ohm}^{-1}\cdot cm^{-1}$. The sign of the thermo-e.m.f. points to hole conductivity. The logarithmic temperature dependence, $\log \sigma = f(10^3/T)$, of specific conductivity at $7 \cdot 10^{-3}\text{ mm Hg}$ shows that dissociation begins at

Card 2/3

Production and investigation...

S/078/62/007/003/019/019
B110/B138

370°C (3.8 ± 0.2 ev). As the valence and conduction bands are far apart, Hg_3Sb_2 is close to the dielectrics. Good absorption properties prove the nonmetallic character of its chemical bond. There are 2 figures and 9 references: 7 Soviet and 2 non-Soviet. The reference to the English-language publication reads as follows: Mellor's Comprehensive Treatise on Inorganic and Theoretical Chemistry, 9, p. 391, 1947.

ASSOCIATION: Voronezhskiy gosudarstvennyy universitet (Voronezh State University)

SUBMITTED: September 28, 1960

Card 3/3

L 23903-65	EWT(m)/EWP(t)/EWP(b)	IJP(c)	JD/JG
ACCESSION NR:	API009355 S/0078/64/009/001/0218/0220		
AUTHOR:	Ugay, Ya.; Gordin, V. L.; Anolkin, V. Z.		
TITLE:	The preparation and certain properties of beryllium antimonide Be_3Sb_2		
SOURCE:	Zhurnal neorganicheskoy khimii, v. 9, no. 1, 1964, 218-220		
TOPIC TAGS:	beryllium antimonide synthesis, beryllium antimonide, property, electric resistance, conductivity, beryllium antimonide		
ABSTRACT:	The study of the Be-Sb system indicates formation of one compound— Be_3Sb_2 . Vaporization in a high vacuum furnace was conducted in graphite cylinders; the beryllium readily dissolves tungsten and tantalum. The formation of a compound between Be and Sb depends on the temperature of the backing. The compound Be_3Sb_2 is stable in air; data on its electric resistance and the temperature-conductivity function are shown in the enclosures. Orig. art. has 2 figures.		
Cord 1/3			

L 23903-65	ACCESSION NR: AP4009355	ASSOCIATION: Voronezhskiy gosudarstvennyy universitet (Voronezh State University)	SUB CODE: /C,GC
SUMMITTED: 11Oct62	ENCL: 01	OTHER: 000	
NO REP SOT: 005			
Card 2/3			

L 14644-66 EWT(1) GM
ACC NR: AT6004295

SOURCE CODE: UR/3175/65/000/026/0044/0048

AUTHOR: Ab, E. A.; Gordin, V. L.; Levitin, A. I.; Filippov, V. A.

29

27

B1

ORG: none

TITLE: A portable source of ultraviolet radiation

SOURCE: USSR. Gosudarstvennyy geologicheskiy komitet. Osoboye konstruktorskoye byuro. Geofizicheskaya apparatura, no. 26, 1965, 44-48

TOPIC TAGS: UV light source, spectral distribution

ABSTRACT: The authors describe a portable radiation source designed for operation in the UV region of the spectrum at about 254 and 320-400 m μ . The spherical envelope of the tube is made from ordinary uvio glass and is about 15 mm in diameter with a wall thickness of the order of fractions of a millimeter. The radiation spectrum of the tube may be expanded by coating the inside of the envelope with a phosphorescent material which emits radiation in the desired spectral region. If part of the surface of the envelope is left uncated (a "window"), the same tube may be used for bidirectional radiation in different spectral regions. Optimum supply fre-

Card 1/2

2

L 14646-56
ACC NR: 11T6004295

frequency was found to be of the order of 100 Mc. A power of the order of 12 w and a frequency of about 100 Mc gave a surface radiation density in the 254 mu range approximately fifty times that of BUV-15 tubes (15 w) and nearly equal to the surface density for PRK tubes. Application of L-33 phosphor increases emission in the 320-400 mu with a surface radiation density approximately 30-40 times that of the UFO-4A tube which has similar spectral distribution. An increase in tube power is not recommended since it may darken or melt the glass of the envelope. Tables and curves are given illustrating the characteristics of spectral distribution for emission from these tubes. The authors are sincerely grateful to L. A. Khutsishvili and N. N. Klimenko for their participation in this work. Orig. art. has: 3 figures, 2 tables.

SUB CODE: 20/ SUBM DATE: 00/ ORIG REF: 004/ OTH REF: 001

Card 2/2 *[Signature]*

L 1855-56 EWT(l)/EPA(s)-2/EWT(m)/EPF(n)-2/T/EWP(t)/EWP(b)/EWA(c) IJP(c)
JD/WW/JJ/CG

ACCESSION NR: AP5022252

UR/0363/65/001/007/1051/1053
546.682'181.1:548.55

AUTHOR: Ugay, Ya. A.; Gordin, V. L.

TITLE: Growing indium phosphide single crystals

SOURCE: AN SSSR. Izvestiya. Neorganicheskiye materialy, v. 1, no. 7, 1965,
1051-1053

TOPIC TAGS: single crystal, indium, indium compound, phosphide, semiconductor
single crystal, single crystal growth, single crystal growing, crystallization,
crystal property, electric property, indium phosphide, melt crystallization, crys-
tal electric property

ABSTRACT: Indium phosphide single crystals have been obtained by a slow
(1.3-1.5 mm/hr) crystallization from melt of stoichiometric composition under
40 atm of phosphorus pressure in a thick-walled horizontal quartz ampul. Origi-
nally, the ampul contained indium and phosphorus separated by a drawn-out portion.
The ampul was heated in a two-zone resistance furnace. A gradual increase in
voltage made possible a gradual progress of crystallization front in the indium
zone of the ampul. The advantages of this technique were stressed in comparison

Card 1/2

L 1855-65

ACCESSION NR: AP5022252

3

with the technique of pulling the crystal from the melt. The x-ray diffraction pattern showed that the ingot obtained was single crystalline over nearly 2/3 of its length. Single crystals 10-12 mm in diameter and 70-100 mm long were obtained. The crystals had an n-type conductivity, thermoelectric power of 150 $\mu\text{v}/\text{deg}$, carrier concentration of $(2.0-3.0) \times 10^{16} \text{ cm}^{-3}$, and a carrier mobility of 6000 $\text{cm}^2/\text{v.sec}$ at room temperature. The latter value exceeded all previously known from the literature and indicated the good quality of the crystals. The electrical characteristics may be improved, e.g., by crucibleless zone-melting. Orig. art. has: 3 figures. [JK]

ASSOCIATION: Voronezhskiy gosudarstvennyy universitet (Voronezh State University)

SUBMITTED: 10Apr65

ENCL: 00

SUB CODE: SS

NO REF Sov: 001

OTHER: 004

ATD PRESS: 4087

G10
Cord 1/2

ACC NR: AP7013719

SOURCE CODE: UR/0154/66/000/001/0079/0083

AUTHOR: Aronov, V. I. (Candidate of physico-mathematical sciences); Gordin,
V. M. (Student)ORG: Moscow State University im. M. V. Lomonosov (Moskovskiy gosudarstvennyy
universitet)TITLE: Computation of the values V_{zz} in a mountainous region

SOURCE: IVUZ. Geodesiya i aerofotos"zemka, no. 1, 1966, 79-83

TOPIC TAGS: Poisson equation, earth gravity

SUB CODE: 08

ABSTRACT: For computing the values V_{zz} from gravity anomalies it is customary to use a formula obtained by differentiation of the Poisson integral for the vertical coordinate. In mountain regions where the observations are made at different elevations the accuracy of computations is low when that formula is used. The errors may be tens or even hundreds of percent of the computed value and in some cases the V_{zz} anomalies may reverse signs. A method was proposed by M. K. Kartvelishvili for computing V_{zz} , taking into account the difference in elevation of stations. The method was based on the M. S. Molodensky equations.

Card 1/2

0033 210

675 - 6797

ACC NR: AP7013719

proposed for computing plumb-line deflections and reduction of gravity anomalies to an external plane, but computations were not given on models characterizing the accuracy of the method. Accordingly, the author of this paper proposes a relatively simple method for computing V_{zz} in a mountainous region. Three examples of computations are given. Even under difficult conditions the accuracy is high. In the case of a large number of iterations the method is equal in accuracy to computations based directly on the theoretical values Δg given on a plane passing directly through the computed point, and in some cases exceeding it. The accuracy in computing V_{zz} in a mountainous region by this method is equal to the accuracy for a lowland region. The same can be demonstrated for the computation of the horizontal derivative of potential and reduction of gravity anomalies. Orig. art. has: 1 figure, 3 formulas and 4 tables.

[JPRS: 40,496]

Card 2/2

1 51997-65	ENG(j)/EWT(1)/EWT(n)/EPF(c)/EPF(n)-2/EPR/T/EWP(t)/EEC(b)-2/EWP(b)/ EWA(c) Pr-1/Ps-1/Pu-1/Pi-1 IJP(c) JD/WJ/JW/JG/GG	UR/0363/65/001/003/0408/0412 546.723'711'21:548.19 56 52
ACCESSION NR:	AP5011939	
AUTHOR: Ya. A.	Tret'yakov, Yu. I.; Spiksonov, Yu. G.; Gordeyev, I. V.; Zayonchkovskiy, Gordina, A. M.	
TITLE:	Correlation between dissociation pressure and crystal lattice parameters of manganese-containing multicomponent ferrites	21
SOURCE:	AN SSSR. Izvestiya. Neorganicheskiye materialy, v. 1, no. 3, 1965, 408-412	
TOPIC TAGS:	manganese ferrite, dissociation, thermal stability, lattice parameter	
ABSTRACT:	An attempt was made to correlate the dissociation pressure of the solid solution ($MnFe_{3-x}O_4$) and the lattice parameter a on the basis of thermodynamic and x-ray data. The object of the study was to develop a method of predicting thermal stability of manganese-containing multicomponent ferrites, materials widely used in the electronic industry and purification technology. Several solid solutions of $MnFe_{3-x}O_4$ ($0 \leq x \leq 3$) containing MgO , ZnO , and CaO were prepared by fusing mixtures of these oxides for 5 hours at 1000°C . Dissociation pressures for several	27
Card	1/2	

L 54997-55			
ACCESSION NR.	AP5011939		
<p>Mn₂Fe₃O₄ solid solutions and temperature range. There is an irregularity between composition and the change of lattice parameter a of the solid (Mn₃O₄). This irregularity is due to interchangeable replacement of iron in magnetite with Mn²⁺ and Mn³⁺ ions. In the 800-1100°C temperature range there is a correlation pressure of the manganese-containing multicomponent ferrites and the crystal lattice parameter a. This correlation is independent of the nature of complementary ferrite. For the Fe₃O₄-MnFeO₄ system, the lattice parameter a increases in proportion to replacement of Fe³⁺ ions ($r=0.67$ Å), in Fe³⁺[Fe²⁺Fe³⁺]O₄ tetrahedra with Mn²⁺ ions ($r=0.91$ Å). In the MnFe₂O₄-Mn₃O₄ system, the changes in the lattice parameter a are small since Fe³⁺ ions are replaced with Mn³⁺ ions ($r=0.70$ Å). Orig. art. has: 2 tables and 3 figures.</p>		<p>mixtures of ferrites were measured in the 800-1200°C range. There is an irregularity between composition and the change of lattice parameter a of the solid (Mn₃O₄) and hausmannite (Fe₃O₄). This irregularity is due to interchangeable replacement of iron in magnetite with Mn²⁺ and Mn³⁺ ions. In the 800-1100°C temperature range there is a correlation pressure of the manganese-containing multicomponent ferrites and the crystal lattice parameter a. This correlation is independent of the nature of complementary ferrite. For the Fe₃O₄-MnFeO₄ system, the lattice parameter a increases in proportion to replacement of Fe³⁺ ions ($r=0.67$ Å), in Fe³⁺[Fe²⁺Fe³⁺]O₄ tetrahedra with Mn²⁺ ions ($r=0.91$ Å). In the MnFe₂O₄-Mn₃O₄ system, the changes in the lattice parameter a are small since Fe³⁺ ions are replaced with Mn³⁺ ions ($r=0.70$ Å). Orig. art. has: 2 tables and 3 figures.</p>	
ASSOCIATION:	Khimicheskiy fakultet Moskovskogo gosudarstvennogo universiteta im. M. V. Lomonosova (Department of Chemistry, Moscow State University)		
SUBMITTED:	01Feb84	ENCL: 0	SUB CODE: EC, SS
NO REF SOV:	006	OTHER: 008	
Card #/2			

TRST'YAKOV, Yu.P.; GORDINA, A.M.

Synthesis of ferrites with a rectangle hysteresis loop from isomorphous
schoenites. Vest. Nauk. in. Ser. 2: Khim. 20 no. 3:67-70 Ny-Je '65.
(MIRA 18:3)

1. Kafedra obshchey khimii Moskovskogo universiteta.

GORDINA, A.P.

GORDINA, A.P.

Rapid method for determining the resistance of tubercle bacilli in sputum to streptomycin and phthivazid. Lab.delo 3 no.6:25-26 N-D '57.
(MIRA 11:1)

1. Iz Khar'kovskogo nauchno-issledovatel'skogo instituta vektsin i syvorotok im. Mechnikova.
(MYCOBACTERIUM TUBERCULOSIS)
(STREPTOMYCIN) (ISONICOTINIC ACID)

GORDINA, G.V.; LAZURENKO, I.S.; KASPAROVA, T.Yu.

Duration of immunity in children inoculated with a whooping cough vaccine. Zhur. mikrobiol., epid. i immun. 33 no.2:33-37 (MIRA 15:3) F '62.

1. Iz Instituta epidemiologii i mikrobiologii imeni N.F. Gamalei AMN SSSR.
(WHOOPING COUGH--PREVENTIVE INOCULATION)

KRAVCHENKO, M., GORDINA, M.

Vowels

New method of treating kymographic curves for making a graph of the movement of basic vowel tones. Vest. Len. un. 6, No. 8, 1951.

9. Monthly List of Russian Accessions, Library of Congress, _____ 1953. Unclassified

FILATOVA, A.D., starshiy nauchnyy sotrudnik; GORDINA, N.L. (Khar'kov)

Vibration neuritis among shoe factory workers. Vrach.delo no.1:
25-29 '60. (MIRA 13:6)

1. Otdel nevrologii (zav. - prof. L.B. Litvak) Ukrainskogo nauchno-
issledovatel'skogo psichonevrologicheskogo instituta.
(SHOEMAKERS--DISEASES AND HYGIENE) (NEURITIS)

MAKSIMOVA, V.G.; YELISEYEVA, K.G.; GORDINA, N.V.; DINERSHTEYN, P.A.

Finishing of wood articles with PE-219N maleic acid polyester
by means of the flow coat method. Lakokras. mat. i ikh prim.
no.4:38-41 '63. (MIRA 16:10)

USSR / Microbiology. Microbes, Pathogenic to Man and Animals. General Problems. F

Abs Jour : Ref Zhur - Biologiya, No 5, 1959, No. 19541

Author : Gordina, P. V.; Lazurenko, I. S.; Remova, T. N.; Silakova, A. V.; Tsatkov, V. S.

Inst : Not given

Title : The Reaction of Whooping Cough and Whooping Cough-Diphtheria Vaccine

Orig Pub : Zh. mikrobiol., epidemiol. i immunobiol., 1958, No 6, 21-26

Abstract : No abstract given

Card 1/1

GORDINA, R. V.

Epidsektora United Inst. Epidemiol. and Microbiol., NKZDRAVA (People's Commissariat of Public Health), (-1944-).

"Analysis of the strains of paratyphus group observed in the USSR (S. paratyphi B and S. typhi inurium)."

Zhur. Mikrobiol., Epidemiol., i Immunobiol., No. 1-2, 1944.

GORDINA, R. V.

Epidemiological sector of TsIEM ~~→~~ Central Inst. of Epidemiology and Microbiology!
(-1944-)

"Differentiation of the Strains of Paratyphus-B Group."

Zhur. Mikrobiol., Epidemiol., i Immunobiol., No. 4-5, 1944.

GORDINA, R. V.

"Phage Types of Paratyphoid B Bacteria, and the Action on Them of Vi Bacteriophage and Others." Proceedings of Inst. Epidem and Microbiol im. Gamaleya 1954-56.

Dissertation Critically Analyzed at Sessions of the Scientific Council During 1953. Inst. Epidem and Microbiol im. Gamaleya AMS USSR

SO: Sum 1186, 11 Jan 57.

Name GORDINA, Raisa Vladimirovna

Dissertation Phagotypes of Paratyphoid B Bacteria
and the affect upon them of Vi-
Bacteriophages

Degree Doc Med Sci

Affiliation /not indicated/

Defense Date, Place 14 Jan 56, Council of the Department
of Hygiene, Microbiology, and
Epidemiology, Acad Med Sci USSR
(2)

Certification Date 29 Dec 56

Source BMVO 7/57

Soviet Prevention of Pertussis, published by Mordovia, 1959
Ed. by N. V. Zhdanov,
Dir. of Specific Prophylaxis of Pertussis,
Mordovia, and Director of the Mordovia
Medical Sch., USSR.

On the epidemiologic performance of pertussis prophylaxis conducted by the Institute of Epidemiology and Microbiology in K. T. Gulyayev's and other institutions and medical establishments, papers were read by (See Table of Contents)

1. N. G. Salnikova (Inst. of Epidemiol. and Microbiol. Dir. N. F. Gulyayev and Mordovia) Problem of pertussis 3
2. N. G. Salnikova and I. S. Lazareva (some on Salnikova's) Effectiveness of pertussis immunization in epidemiologic observations 19
3. N. A. Melikyan (Inst. Biomed. Inst. in E. T. Pirogov's) Clinical epidemiologic effectiveness of the pertussis vaccine in epidemics 29
4. A. V. Shabotov (Inst. of Pediatrics and MDRB); Clinical study of reactions in children vaccinated with pertussis vaccines 37
5. A. B. Filimonova et al. (Inst. of Hygiene, Mikrobiol., and Epidemiol. and Sanit. for Children of Mordovia and Children of the Mordovian SSR); Study of the effectiveness of immunization against pertussis 43
6. G. Salnikova and N. I. Ryabtseva (Central Scientific Inst. of Hygiene and Epidemiology of the Ministry of Communications USSR); Effectiveness of vaccination with pertussis vaccine among residents in the Moscow Railways' Bureau 53
7. B. T. Grudzinskaya et al. (Chairty Scientific Res. Inst. for Vaccines and Serums); Effectiveness of vaccination against pertussis in epidemiologic observations 59
8. N. V. Gurevich and T. N. Komaroff (see above); Epidemiologic effectiveness of pertussis-diphtheria vaccines 63
9. L. A. Salnikova (Sovietic Sanitary-Epidemiologic Station of the Ministry of Health of the Georgian SSR); Epidemiologic and immunologic effectiveness and toxicogenicity of the pertussis-diphtheria vaccine 70
10. N. G. Salnikova et al. (Inst. of Hygiene and Epidemiol. and Mordovia); Toxicogenicity and epidemiologic effectiveness of pertussis and pertussis-diphtheria vaccine 87
11. N. A. Salnikova (Mordovia Inst. of Epidemiol. and Hygiene in Piatrov); Data on reactogenicity and immunologic and epidemiologic effectiveness of the pertussis and pertussis-diphtheria vaccine 93
12. G. G. Tsygankova et al. (The Central, etc. see Epidemiology above); Effectiveness in the use of pertussis and pertussis-diphtheria vaccine in Children's Institutions of the Railroads Transport System 101
13. V. A. Salnikova (Sovietic Sanitary-Epidemiologic Station of the Moldavian SSR); Study of reactogenicity and epidemiologic effectiveness of pertussis and pertussis-diphtheria vaccine 111

GORDINA, R.V. doktor med.nauk (Moskva)

Specific prevention of whooping cough. Fel'd. i akush. 23 no.12:
24-26 D '58 (MIRA 11:12)
(WHOOPING COUGH)